

**Safety Data Sheet**  
prepared to UN GHS Revision 3



## 1. Identification of the Substance/Mixture and the Company/Undertaking

- |   |  |  |                         |            |
|---|--|--|-------------------------|------------|
| <b>1.1</b>  | <b>Product Identifier</b>  | 9250A0   | <b>Revision Date:</b>   | 07/05/2015 |
|   | <b>Product Name:</b>   | Epoplex LS65qs White   | <b>Supersedes Date:</b> | 07/05/2015 |
| <b>1.2</b>  | <b>Relevant identified uses of the substance or mixture and uses advised against</b> | Base component of 2 components coatings - Industrial use.  |                         |            |
| <b>1.3 Details of the supplier of the safety data sheet</b> |  |  |                         |            |
|   | <b>Manufacturer:</b>   | EPOPLEX, A DIVISION OF STONCOR GROUP, INC<br>1000 EAST PARK AVENUE<br>MAPLE SHADE, NJ 08052<br><br>+1 856 7797500 (US) |                         |            |
|   | <b>Datasheet Produced by:</b>  | Darnell, Benjamin - ehs@stoncor.com  |                         |            |
| <b>1.4</b>  | <b>Emergency telephone number:</b>   | CHEMTREC 1-800-424-9300 (Inside US)<br>CHEMTREC +1 703 5273887 (Outside US)  |                         |            |

## 2. Hazard Identification

### 2.1 Classification of the substance or mixture

Hazardous to the aquatic environment, Chronic, category 2  
 Eye Irritation, category 2  
 Skin Irritation, category 2  
 Skin Sensitizer, category 1

### 2.2 Label elements

#### Symbol(s) of Product



#### Signal Word

Warning

#### Named Chemicals on Label

2-ethylhexyl glycidyl ether, reaction product: bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)

**HAZARD STATEMENTS**

Hazardous to the aquatic environment, Chronic, category 2	H411	Toxic to aquatic life with long lasting effects.
Eye Irritation, category 2	H319	Causes serious eye irritation.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.

**PRECAUTION PHRASES**

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P273	Avoid release to the environment
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+352	IF ON SKIN: Wash with plenty of soap and water.
P305+351+338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do so. Continue rinsing.
P332+313	If skin irritation occurs: Get medical advice/attention.
P333+313	If skin irritation or rash occurs: Get medical advice/attention.
P391	Collect spillage.

**2.3 Other hazards**

Not applicable

**Results of PBT and vPvB assessment**

The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

**3. Composition/Information On Ingredients****3.2 Mixtures****Hazardous Ingredients**

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>%</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	25-50
13463-67-7	titanium dioxide	25-50
2461-15-6	2-ethylhexyl glycidyl ether	2.5-10
7631-86-9	silicon dioxide (amorphous)	2.5-10

<u>CAS-No.</u>	<u>GHS Symbols</u>	<u>GHS Hazard Statements</u>	<u>MFactors</u>
25068-38-6	GHS07-GHS09	H315-317-319-411	0
13463-67-7			0
2461-15-6	GHS07	H315-317-319	0
7631-86-9			0

**Additional Information:** The text for GHS Hazard Statements shown above (if any) is given in Section 16.**4. First-aid Measures****4.1 Description of First Aid Measures****GENERAL NOTES:** When symptoms persist or in all cases of doubt seek medical advice.**AFTER INHALATION:** Move to fresh air. Consult a physician after significant exposure.**AFTER SKIN CONTACT:** Use a mild soap if available. Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. If skin irritation persists, call a physician.**AFTER EYE CONTACT:** Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Remove contact lenses. If eye irritation persists, consult a specialist.**AFTER INGESTION:** Gently wipe or rinse the inside of the mouth with water. Give small amounts of water to drink. Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

**Self protection of the first aider:**

No action shall be taken involving any personal risk or without suitable training. It may be dangerous to the person providing aid to give mouth-to-mouth resuscitation. Wash contaminated clothing thoroughly with water before removing it, or wear gloves.

**4.2 Most important symptoms and effects, both acute and delayed**

Irritating to skin. May cause sensitization by skin contact. Prolonged or repeated exposure increases the risk. Harmful to aquatic organisms.

**4.3 Indication of any immediate medical attention and special treatment needed**

No information available on clinical testing and medical monitoring. Specific toxicological information on substances, if available, can be found in section 11.

**5. Fire-fighting Measures****5.1 Extinguishing Media:**

Carbon Dioxide, Dry Chemical, Foam

**FOR SAFETY REASONS NOT TO BE USED:** Alcohol, Alcohol based solutions, any other media not listed above.

**5.2 Special hazards arising from the substance or mixture**

No Information

**5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus. High volume water jet. Hazardous decomposition products formed under fire conditions. Collect contaminated fire extinguishing water separately. This must not be discharged into drains. Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Contains epoxy constituents. See information supplied by the manufacturer.

**6. Accidental Release Measures****6.1 Personal precautions, protective equipment and emergency procedures**

Ensure adequate ventilation. Use personal protective equipment

**6.2 Environmental precautions**

Do not allow material to contaminate ground water system. Prevent product from entering drains. May cause long-term adverse effects in the aquatic environment

**6.3 Methods and material for containment and cleaning up**

Prevent further leakage or spillage if safe to do so. Contain spillage, soak up with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).

**6.4 Reference to other sections**

Please refer to disposal requirements or country specific disposal requirements for this material. See Section 13 for further information.

**7. Handling and Storage****7.1 Precautions for safe handling**

**INSTRUCTIONS FOR SAFE HANDLING:** Use only in area provided with appropriate exhaust ventilation. Wear personal protective equipment

**PROTECTION AND HYGIENE MEASURES:** Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

**CONDITIONS TO AVOID:** Extremes of temperature and direct sunlight

**STORAGE CONDITIONS:** Store in original container. Keep locked up or in an area accessible only to qualified or authorised persons. Store in a dry, well ventilated place away from sources of heat, ignition and direct sunlight

**7.3 Specific end use(s)**

No specific advice for end use available.

## 8. Exposure Controls/Personal Protection

### 8.1 Control parameters

#### Ingredients with Occupational Exposure Limits (US)

<u>Name</u>	<u>%</u>	<u>OSHA PEL</u>	<u>ACGIH TLV</u>
reaction product: bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	25-50		
titanium dioxide	25-50	15.0 mg/m3	
2-ethylhexyl glycidyl ether	2.5-10		
silicon dioxide (amorphous)	2.5-10	15.0 mg/m3	

**FURTHER INFORMATION:** Refer to the regulatory exposure limits for the workforce enforced in each country.

### 8.2 Exposure controls

#### Personal Protection

**RESPIRATORY PROTECTION:** No personal respiratory protective equipment normally required.

**EYE PROTECTION:** Safety glasses.

**HAND PROTECTION:** Rubber or plastic gloves. Take note of the information given by the producer concerning permeability and break through times, and of special workplace conditions (mechanical strain, duration of contact). Long sleeved clothing. Remove and wash contaminated clothing before re-use. Rubber or plastic apron.

**OTHER PROTECTIVE EQUIPMENT:** No Information

**ENGINEERING CONTROLS:** Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas.

## 9. Physical and Chemical Properties

### 9.1 Information on basic physical and chemical properties

Appearance:	WHITE RESIN
Physical State	LIQUID
Odor	FAINT EPOXY ODOR
Odor threshold	Not determined
pH	NON-AQUEOUS
Melting point /freezing point (°C)	Not determined
Boiling point/range (°C)	150 - N.D.
Flash Point, (°F /°C)	>210F />99C
Evaporation rate	Not determined
Flammability (solid, gas)	Not determined
Upper/lower flammability or explosive limits	NOT DETERMINED - NOT DETERMINED
Vapour Pressure	NOT DETERMINED
Vapour density	NOT DETERMINED
Relative density	Not determined
Solubility in /Miscibility with water	NEGLECTIBLE
Partition coefficient: n-octanol/water	Not determined
Auto-ignition temperature (°C)	Not determined
Decomposition temperature (°C)	

	Not determined
<b>Viscosity</b>	N/A
<b>Explosive properties</b>	Not determined
<b>Oxidising properties</b>	Not determined

**9.2 Other information**

<b>VOC Content g/l:</b>	5
<b>Specific Gravity (g/cm<sup>3</sup>)</b>	0.000

## 10. Stability and Reactivity

**10.1 Reactivity**

No reactivity hazards known under normal storage and use conditions.

**10.2 Chemical stability**

No decomposition if stored and applied as directed. Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous polymerisation does not occur.

**10.4 Conditions to avoid**

Extremes of temperature and direct sunlight.

**10.5 Incompatible materials**

Strong oxidizing agents. Acids and bases. Amines.

**10.6 Hazardous decomposition products**

Thermal decomposition can lead to release of irritating gases and vapours. Alcohols. Exothermic reaction. Carbon dioxide (CO<sub>2</sub>), carbon monoxide (CO), oxides of nitrogen (NO<sub>x</sub>), dense black smoke.

## 11. Toxicological Information

**11.1 Information on toxicological effects****Acute Toxicity:**

Oral LD50:

Inhalation LC50:

**Irritation:** No information available.

**Corrosivity:** No information available.

**Sensitization:** No information available.

**Repeated dose toxicity:** No information available.

**Carcinogenicity:** No information available.

**Mutagenicity:** No information available.

**Toxicity for reproduction:** No information available.

If no information is available above under Acute Toxicity then the acute effects of this product have not been tested. Data on individual components are tabulated below.

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	>2000 mg/kg, rat, oral	>2000 mg/kg, rat	
13463-67-7	titanium dioxide	10000 mg/m3, oral (rat)		
2461-15-6	2-ethylhexyl glycidyl ether	7800 mg/kg, rat	>2000 mg/kg, rabbit	

**Additional Information:**

This product may contain Titanium Dioxide, which is listed by IARC as possibly carcinogenic to humans (Group 2B). This listing is based on inadequate evidence of carcinogenicity in humans and sufficient evidence in experimental animals. This classification is relevant when exposed to titanium dioxide in dust or powder form only, including cured product that is subject to sanding, grinding, cutting, or other surface preparation activities.

## 12 Ecological Information

**12.1 Toxicity:**

<b>EC50 48hr (Daphnia):</b>	No information
<b>IC50 72hr (Algae):</b>	No information
<b>LC50 96hr (fish):</b>	No information

**12.2 Persistence and degradability:** No information

**12.3 Bioaccumulative potential:** No information

**12.4 Mobility in soil:** No information

**12.5 Results of PBT and vPvB assessment:** The product does not meet the criteria for PBT/vPvB in accordance with Annex XIII.

**12.6 Other adverse effects:** No information

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>EC50 48hr</u>	<u>IC50 72hr</u>	<u>LC50 96hr</u>
25068-38-6	reaction product bisphenol-a-(epichlorhydrin) epoxy resin (number average molecularweight <= 700)	No information	No information	1.5-7.7 mg/L
13463-67-7	titanium dioxide	>100 mg/l (EC50, 48h, Daphnia magna OECD202)ation	No information	>1000 mg/l
2461-15-6	2-ethylhexyl glycidyl ether	No information	No information	
7631-86-9	silicon dioxide (amorphous)	No information	No information	

## 13. Disposal Considerations

**13.1 WASTE TREATMENT METHODS:** If recycling is not practicable, dispose of in compliance with local regulations. Dispose of wastes in an approved waste disposal facility. Empty containers should be taken to an approved waste handling site for recycling or disposal.

## 14. Transport Information

14.1	UN number	UN3082
14.2	UN proper shipping name	Environmentally Hazardous Substance, Liquid, N.O.S.
	Technical name	reaction product: bisphenol-a-(epichlorhydrin) epoxy resin
14.3	Transport hazard class(es)	9
	Subsidiary shipping hazard	
14.4	Packing group	III
14.5	Environmental hazards	
14.6	Special precautions for user	For professional use only.
	EmS-No.:	N/A
14.7	Transport in bulk according to Annex II of MARPOL 73/78 and the IBC code	Not applicable

## 15. Regulatory Information

15.1 Safety, health and environmental regulations/legislation for the substance or mixture:

### U.S. Federal Regulations: As follows -

#### CERCLA - Sara Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Acute Health Hazard

#### Sara Section 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the U.S. Superfund Amendment and Reauthorization Act (SARA) of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product

#### Toxic Substances Control Act

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

<u>Chemical Name</u>	<u>CAS-No.</u>
mequinol	150-76-5

#### U.S. Clean Air Act

EPA Coating Category:	TRAFFIC MARKING COATINGS
EPA VOC Content Limit (g/l):	150
Product VOC Content (g/l)	5.0
Thinning Recommendations:	NONE
Application Recommendations:	FOR PROFESSIONAL USE ONLY.

\* As per the federal EPA definition for coating categories in 40 CFR 59.401.

\*\* Grams of VOC per liter of coating product as applied (mixture of Part A and Part B) per ASTM D2369 Method E.

### U.S. State Regulations: As follows -

#### New Jersey Right-to-Know

The following materials are non-hazardous, but are among the top five components in this product.

<u>Chemical Name</u>	<u>CAS-No.</u>
acrylated resin	18275200000-5196
acrylate mixture	18275200000-5197

## Pennsylvania Right-To-Know

The following non-hazardous ingredients are present in the product at greater than 3%.

<u>Chemical Name</u>	<u>CAS-No.</u>
acrylated resin	18275200000-5196
acrylate mixture	18275200000-5197

## California Proposition 65:

Warning: The following ingredients present in the product are known to the State of California to cause cancer:

<u>Chemical Name</u>	<u>CAS-No.</u>
titanium dioxide	13463-67-7

Warning: The following ingredients present in the product are known to the State of California to cause birth defects, or other reproductive hazards.

No Proposition 65 Reproductive Toxins exist in this product

## International Regulations: As follows -

### \* Canadian DSL:

All chemical ingredients included on inventory or exempt.

### 15.2 Chemical Safety Assessment

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

## 16. Other Information

### Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H411	Toxic to aquatic life with long lasting effects.

### Reasons for revision

This Safety Data Sheet (SDS) has been revised to meet updated national hazard communication standards which have adopted the provisions of the UN GHS system. There have been both formatting and content changes based on the GHS classification (if applicable), Please review each section of the SDS for specific changes.

### List of References:

This Safety Data Sheet was compiled with data and information from the following sources:

The Ariel Regulatory Database provided by the 3E Corporation in Copenhagen, Denmark  
 ESIS (The European Chemical Substances Information System), provided by the European Commission  
 Joint Research Centre in Ispra, Italy  
 Annex VI of the EU Council Directive 67/548/EEC  
 Council Directive 67/548/EEC - Annex I or EU Council Directive 1999/45/EC  
 European Union (EC) Regulation No. 1272/2008 on the classification, labelling and packaging of substances and mixtures (CLP Regulation)  
 EU Council Decision 2000/532/EC and its Annex entitled "List of Wastes"

### Acronym & Abbreviation Key:

CLP	Classification, Labeling & Packaging Regulation
EC	European Commission



EU	European Union
US	United States
CAS	Chemical Abstract Service
EINECS	European Inventory of Existing Chemical Substances
REACH	Registration, Evaluation, Authorization of Chemicals Regulation
GHS	Globally Harmonized System of Classification and Labeling of Chemicals
LTEL	Long term exposure limit
STEL	Short term exposure limit
OEL	Occupational exposure limit
ppm	Parts per million
mg/m3	Milligrams per cubic meter
TLV	Threshold Limit Value
ACGIH	American Conference of Governmental Industrial Hygienists
OSHA	Occupational Safety & Health Administration
PEL	Permissible Exposure Limits
VOC	Volatile organic compounds
g/l	Grams per liter
mg/kg	Milligrams per kilogram
N/A	Not applicable
LD50	Lethal dose at 50%
LC50	Lethal concentration at 50%
EC50	Half maximal effective concentration
IC50	Half maximal inhibitory concentration
PBT	Persistent bioaccumulative toxic chemical
vPvB	Very persistent and very bioaccumulative
EEC	European Economic Community
ADR	International Transport of Dangerous Goods by Road
RID	International Transport of Dangerous Goods by Rail
UN	United Nations
IMDG	International Maritime Dangerous Goods Code
IATA	International Air Transport Association
MARPOL	International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978
IBC	International Bulk Container

For further information, please contact: Technical Services Department

The information on this sheet corresponds to our present knowledge. It is not a specification and it does not guarantee specific properties. The information is intended to provide general guidance as to health and safety based upon our knowledge of the handling, storage, and use of the product. It is not applicable to unusual or non-standard uses of the product or where instructions and recommendations are not followed.